

XQ-S9150D 工业级舵机 2000 小时 寿命测试白皮书（中英文对照版）

XQ-S9150D Industrial Grade Servo 2000-Hour Life Test White Paper (Chinese-English Version)

XQ-S9150D 工业级无刷舵机

XQ-S9150D Industrial Grade Brushless Servo

2000 小时长期寿命测试白皮书

2000-Hour Long-Term Life Test White Paper

(可对外发布版)

(Public Release Version)

文档版本：V2.0

Document Version: V2.0

发布日期：2026-05-20

Release Date: 2026-05-20

测试单位：XQPOWER 可靠性实验室

Testing Unit: XQPOWER Reliability Laboratory

联系人：[周先生]

Contact Person: [Fill in Contact Person's Name]

联系电话：[+86-755-26910992]

Contact Phone: [+86-755-26910992]

邮箱：[info@cnxqpower.com]

Email: [info@cnxqpower.com]

目 录 / Table of Contents

1. 摘要 (Executive Summary)	1
2. 产品概述 (Product Overview)	2
2.1 产品定位 (Product Positioning)	2
2.2 关键规格 (Key Specifications)	2
3. 测试目的与范围 (Test Objective & Scope)	3
3.1 测试目的 (Test Objective)	3
3.2 测试范围 (Test Scope)	3
4. 测试环境与设备 (Test Environment & Equipment)	4
4.1 环境条件 (Environmental Conditions)	4
4.2 测试设备清单 (Test Equipment List)	4
5. 测试方案与流程 (Test Methodology)	5
5.1 测试剖面 (2000 小时分段) (Test Profile (2000-Hour Segmentation))	5
5.2 失效判定标准 (工业级) (Failure Criteria (Industrial Grade))	5
5.3 数据采集频率 (Data Collection Frequency)	6
6. 测试结果 (Test Results)	7
6.1 总体结果 (Overall Results)	7
6.2 关键性能衰减对比 (2000h vs 初始) (Comparison of Key Performance Attenuation (2000h vs Initial))	7
6.3 失效模式分析 (Failure Mode Analysis)	8
6.4 寿命推算 (基于加速老化模型) (Service Life Estimation (Based on Accelerated Aging Model))	9
7. 结论与应用建议 (Conclusion & Recommendations)	10
7.1 测试结论 (Test Conclusions)	10
7.2 应用推荐 (Application Recommendations)	10
7.3 使用建议 (Usage Recommendations)	11
8. 附录 (Appendix)	12
附录 A: 测试原始数据记录表 (每 100 小时) (Appendix A: Test Raw Data Record Form (Every 100 Hours))	12

附录 B: 2000 小时性能参数变化曲线 (Appendix B: 2000-Hour Performance Parameter Change Curves) 14

附录 C: 样品拆解检查照片 (Appendix C: Sample Disassembly Inspection Photos) 15

附录 D: 参考标准清单 (Appendix D: List of Reference Standards) 16

1. 摘要 (Executive Summary)

XQ-S9150D 是 XQPOWER 面向工业自动化、重型机械臂、排爆机器人、大型无人设备等高端工业场景，自主研发的工业级重载无刷舵机。该产品采用磁编码器+全金属强化齿轮+军工级密封结构设计，额定输出扭矩达 50kg·cm (@8.4V)，具备低发热、低漂移、高防护、长寿命的核心优势，专为长期连续运行的工业场景量身打造。

XQ-S9150D is an industrial-grade heavy-duty brushless servo independently developed by XQPOWER for high-end industrial scenarios such as industrial automation, heavy-duty robotic arms, explosive ordnance disposal robots, and large-scale unmanned equipment. Adopting a design of magnetic encoder + full metal reinforced gear + military-grade sealing structure, the product has a rated output torque of 50kg·cm (@8.4V), with core advantages of low heat generation, low drift, high protection, and long service life, tailored for industrial scenarios requiring long-term continuous operation.

为验证 **XQ-S9150D** 工业级长期可靠性，XQPOWER 可靠性实验室严格按照 GB/T 40729-2021、IEC 60034 等工业标准，对该型号舵机开展了累计 2000 小时的连续寿命测试。测试覆盖额定负载、高温、湿热、振动等复合工况，模拟真实工业现场 5–8 年的实际使用强度，全面评估产品在长期运行后的性能稳定性与失效风险。

To verify the industrial-grade long-term reliability of XQ-BLS9150D, XQPOWER Reliability Laboratory has conducted a cumulative 2000-hour continuous life test on this type of servo in strict accordance with industrial standards such as GB/T 40729-2021 and IEC 60034. The test covers composite working conditions such as rated load, high temperature, damp heat, and vibration, simulating the actual service intensity of 5–8 years in real industrial sites, to comprehensively evaluate the performance stability and failure risk of the product after long-term operation.

核心测试结论：

Core Test Conclusions:

在标准工业工况下，**XQ-S9150D** 连续运行 2000 小时无任何样品失效，定位精度、扭矩输出、响应速度等关键性能衰减均控制在≤8%，完全满足并超越工业级舵机 2000 小

时 MTBF（平均无故障时间）要求，可长期稳定应用于重载、高频、恶劣环境下的工业场景，为客户设备的高可靠性运行提供核心保障。

Under standard industrial working conditions, XQ-**XQ-S9150D** has been continuously operating for 2000 hours without any sample failure. The attenuation of key performances such as positioning accuracy, torque output, and response speed is controlled within $\leq 8\%$, which fully meets and exceeds the 2000-hour MTBF (Mean Time Between Failures) requirement for industrial-grade servos. It can be stably applied to industrial scenarios with heavy load, high frequency, and harsh environment for a long time, providing core guarantee for the high-reliability operation of customers' equipment.

2. 产品概述 (Product Overview)

2.1 产品定位 (Product Positioning)

XQ-S9150D 定位为工业级重载长寿命无刷舵机，聚焦高端工业自动化领域，解决传统舵机在重载工况下寿命短、精度漂移、易失效的行业痛点，适配各类对可靠性、耐久性要求极高的工业设备，具体应用场景包括但不限于：

XQ-S9150D is positioned as an **industrial-grade heavy-duty long-life brushless servo**, focusing on the high-end industrial automation field. It solves the industry pain points of traditional servos such as short service life, precision drift, and easy failure under heavy load conditions, and is suitable for various industrial equipment with high requirements for reliability and durability. Specific application scenarios include but are not limited to:

- 重型机械臂、多轴工业操作平台 / Heavy-duty robotic arms, multi-axis industrial operation platforms
- 排爆机器人、特种作业机器人 / Explosive ordnance disposal robots, special operation robots
- 大型无人车、无人船、工业 AGV / Large-scale unmanned vehicles, unmanned ships, industrial AGVs
- 工业重载云台、自动化生产线执行机构 / Industrial heavy-duty pan-tilt, executive mechanisms of automated production lines
- 高可靠、免维护工业控制设备 / High-reliability, maintenance-free industrial control equipment

2.2 关键规格（简述） (Key Specifications (Brief))

参数名称 / Parameter Name	参数值 / Parameter Value	备注 / Remarks
产品型号 / Product Model	XQ-S9150D	工业级无刷高压版本 / Industrial-grade brushless high-voltage version
电机类型 / Motor Type	无刷直流电机 (Brushless DC Motor)	低磨损、低发热、长寿命 / Low wear, low heat generation, long service life
编码器类型 / Encoder Type	磁编码器 (360°无死区) / Magnetic Encoder (360° No Dead Zone)	高精度、无接触磨损、抗干扰 / High precision, no contact wear, anti-interference
额定扭矩 (@8.4V) / Rated Torque (@8.4V)	50kg·cm] 50kg·cm]	可根据测试数据调整 / Adjustable according to test data
响应速度 (@8.4V) / Response Speed (@8.4V)	0.14s/60°] 0.14s/60°]	无负载状态下测试 / Tested under no-load condition
工作电压范围 / Operating Voltage Range	6.0–8.4V DC	宽压适配, 支持工业常用高压 / Wide voltage adaptation, supporting commonly used industrial high voltage
防护等级 / Protection Level	IP67	防尘、防水, 适配恶劣工业环境 / Dustproof and waterproof, suitable for harsh industrial environments
齿轮结构 / Gear Structure	全金属强化钢齿轮组 / Full Metal Reinforced Steel Gear Set	抗冲击、抗磨损, 适配重载 / Impact resistance, wear resistance, suitable

		for heavy load
设计寿命 / Design Life	≥2000 小时连续运行 / ≥2000 hours of continuous operation	工业级标准，基于模拟工 况测试 / Industrial-grade standard, based on simulated working condition test
工作温度范围 / Operating Temperature Range	-20℃ ~ +60℃	短期可耐受 70℃ 高温 / Can withstand 70℃ high temperature for a short time

3. 测试目的与范围 (Test Objective & Scope)

3.1 测试目的 (Test Objective)

本次 2000 小时寿命测试，核心目的是全面验证 **XQ-S9150D** 舵机的工业级长期可靠性，为产品对外推广、客户选型提供科学、权威的测试数据支撑，具体包括：

The core purpose of this 2000-hour life test is to comprehensively verify the industrial-grade long-term reliability of **XQ-S9150D** servo, providing scientific and authoritative test data support for product promotion and customer selection, including:

1. 验证 **XQ-S9150D** 在长期连续负载工况下的耐久性与运行稳定性，确认产品是否达到设计寿命要求。 / Verify the durability and operational stability of **XQ-S9150D** under long-term continuous load conditions, and confirm whether the product meets the design life requirements.
2. 评估产品连续运行 2000 小时后，关键性能（定位精度、扭矩输出、响应速度、发热等）的衰减程度，判断是否满足工业级应用标准。 / Evaluate the attenuation degree of key performances (positioning accuracy, torque output, response speed, heat generation, etc.) after the product has been continuously operating for 2000 hours, and judge whether it meets the industrial-grade application standards.
3. 排查产品在长期运行中的潜在失效模式，重点分析齿轮、轴承、无刷电机、驱动板、密封结构的可靠性。 / Identify potential failure modes of the product during long-term operation, focusing on analyzing the reliability of gears, bearings, brushless motors, driver boards, and sealing structures.
4. 建立 **XQ-S9150D** 工业级应用的寿命基准与可靠性数据，为客户系统设计、维护

周期规划提供参考。 / Establish the life benchmark and reliability data of **XQ-S9150D** for industrial-grade applications, providing reference for customer system design and maintenance cycle planning.

5. 验证产品在高温、湿热、振动等恶劣工业环境下的适应能力，确保其在复杂场景中的长期稳定运行。 / Verify the adaptability of the product in harsh industrial environments such as high temperature, damp heat, and vibration, ensuring its long-term stable operation in complex scenarios.

3.2 测试范围 (Test Scope)

测试项目 / Test Item	具体内容 / Specific Content
测试样品 / Test Samples	同批次 XQ-S9150D 舵机，N=5 台（随机抽样，确保样品代表性） / 5 servos of the same batch XQ-BLS9150D, N=5 (random sampling to ensure sample representativeness)
测试项目 / Test Items	连续负载寿命测试、高温耐久测试、湿热循环测试、振动耐久测试、极限循环测试 / Continuous load life test, high temperature durability test, damp heat cycle test, vibration durability test, extreme cycle test
测试时长 / Test Duration	单台样品累计 2000 小时连续运行，5 台样品累计测试时长 10000 小时 / Each sample runs continuously for a cumulative 2000 hours, and the total test duration of 5 samples is 10000 hours
测试依据 / Test Basis	GB/T 40729-2021《机器人用伺服系统通用技术条件》、GB/T 2423《电工电子产品环境试验》、IEC 60034《旋转电机 定额和性能》、ISO 12100《机械安全 设计通则》 / GB/T 40729-2021 "General Technical Conditions for Servo Systems for Robots", GB/T 2423 "Environmental Testing for Electrical and Electronic Products", IEC 60034 "Rotating Electrical Machines - Ratings and Performance", ISO 12100 "Mechanical Safety - General Principles for Design"
判定标准 / Judgment Standard	参照工业级舵机失效判据，明确失效阈值（详见第 5.2 节） / Refer to the failure criteria of industrial-grade servos, and clarify the failure threshold (see Section 5.2 for details)

4. 测试环境与设备 (Test Environment & Equipment)

4.1 环境条件 (工业模拟工况) (Environmental Conditions (Industrial Simulated Working Conditions))

本次测试采用“复合应力加速老化”模式，模拟真实工业现场的运行环境，分阶段设置不同测试条件，确保测试结果的真实性与参考价值，具体环境参数如下：

This test adopts the "composite stress accelerated aging" mode to simulate the operating environment of real industrial sites, setting different test conditions in stages to ensure the authenticity and reference value of the test results. The specific environmental parameters are as follows:

测试阶段 / Test Stage	温度 / Temperature	湿度 / Humidity	供电条件 / Power Supply Condition	负载条件 / Load Condition	运动参数 / Motion Parameters
常温额定负载段 / Normal Temperature Rated Load Stage	25℃ ±5℃	50%RH ±10%RH	8.4V 稳压 直流 / 8.4V Regulated DC	70%额定扭矩 / 70% Rated Torque	0°–180°往复, 1 次/秒 (1Hz) / 0°– 180° Reciprocating, 1 time/second (1Hz)
高温耐久段 / High Temperature Durability Stage	45℃ ±2℃	50%RH ±10%RH	8.4V 稳压 直流 / 8.4V Regulated DC	70%额定扭矩 / 70% Rated Torque	0°–180°往复, 1 次/秒 (1Hz) / 0°– 180° Reciprocating, 1 time/second (1Hz)
湿热循环段 / Damp Heat Cycle	40℃ ±2℃	85%RH ±5%RH	8.4V 稳压 直流 / 8.4V Regulated	50%额定扭矩 / 50% Rated	0°–180°往复, 1 次/秒 (1Hz) / 0°–

Stage			DC	Torque	180° Reciprocating, 1 time/second (1Hz)
振动+极限 循环段 / Vibration + Extreme Cycle Stage	25°C ±5°C	50%RH ±10%RH	8.4V 稳压 直流 / 8.4V Regulated DC	50%额定扭 矩 / 50% Rated Torque	0°–180°往复, 1.5 次/秒 (1.5Hz), 振 动 10–200Hz (随机) / 0°– 180° Reciprocating, 1.5 times/second (1.5Hz), Vibration 10– 200Hz (Random)

注：供电采用工业级稳压电源，确保电压波动 $\leq \pm 0.1V$ ，模拟工业现场稳定供电环境；负载采用程控加载方式，实时保持设定负载值，避免负载波动影响测试结果。

Note: The power supply adopts an industrial-grade regulated power supply to ensure that the voltage fluctuation is $\leq \pm 0.1V$, simulating a stable power supply environment in industrial sites; the load adopts a program-controlled loading method to maintain the set load value in real time, avoiding the impact of load fluctuation on the test results.

4.2 测试设备清单 (Test Equipment List)

本次测试均采用符合工业标准的高精度测试设备，确保测试数据的准确性与权威性，具体设备清单如下：

This test uses high-precision test equipment that meets industrial standards to ensure the accuracy and authority of the test data. The specific equipment list is as follows:

设备名称 / Equipment Name	设备规格 / Equipment Specifications	用途 / Purpose
工业伺服寿命测试台 / Industrial Servo Life Test Bench	可编程负载 (0–100kg·cm)、角度闭环控制 / Programmable load	实现舵机连续负载运行、角度往复控制，模拟实际工作状态 / Realize continuous load

	(0–100kg·cm), angle closed-loop control	operation and angle reciprocating control of the servo, simulating the actual working state
高低温湿热箱 / High and Low Temperature Damp Heat Chamber	温度范围: -40℃ ~ +85℃; 湿度范围: 20%–98%RH / Temperature range: -40℃ ~ +85℃; Humidity range: 20%–98%RH	模拟高温、湿热等恶劣工业环境, 开展环境耐久测试 / Simulate harsh industrial environments such as high temperature and damp heat, and carry out environmental durability tests
电磁振动台 / Electromagnetic Vibration Table	频率范围: 10–1000Hz; 振动方式: 随机/正弦振动 / Frequency range: 10–1000Hz; Vibration mode: Random/Sinusoidal vibration	模拟工业设备运行中的振动环境, 验证舵机抗振动能力 / Simulate the vibration environment during the operation of industrial equipment, and verify the vibration resistance of the servo
高精度扭矩传感器 / High Precision Torque Sensor	量程: 0–100kg·cm; 精度: ±1%FS / Range: 0–100kg·cm; Accuracy: ±1%FS	实时监测舵机输出扭矩, 记录扭矩变化数据 / Real-time monitor the output torque of the servo and record torque change data
角度编码器 / Angle Encoder	精度: ±0.1°; 测量范围: 0°–360° / Accuracy: ±0.1°; Measurement range: 0°–360°	监测舵机定位精度、角度往复一致性, 记录精度变化 / Monitor the positioning accuracy and angle reciprocating consistency of the servo, and record the accuracy change
数据采集系统 / Data Acquisition System	采样频率: 10 次/秒; 可同步记录多参数 / Sampling frequency: 10 times/second; Can record multiple parameters synchronously	同步采集舵机角度、扭矩、电流、表面温度等数据, 生成实时曲线 / Synchronously collect data such as servo angle, torque, current, and surface temperature, and

		generate real-time curves
工业级稳压电源 / Industrial-grade Regulated Power Supply	输出电压：0–30V；输出 电流：0–20A；稳压精 度：±0.1V / Output voltage: 0–30V; Output current: 0–20A; Voltage regulation accuracy: ±0.1V	为舵机提供稳定供电，避免电 压波动影响测试结果 / Provide stable power supply for the servo to avoid the impact of voltage fluctuation on the test results
红外测温仪 / Infrared Thermometer	测量范围：-50℃ ~ +300℃；精度：±0.5℃ / Measurement range: - 50℃ ~ +300℃; Accuracy: ±0.5℃	实时监测舵机表面温度，排查 过热风险 / Real-time monitor the surface temperature of the servo and check for overheating risks

5. 测试方案与流程（Test Methodology）

5.1 测试剖面（2000 小时分段）（Test Profile (2000-Hour Segmentation)）

本次 2000 小时寿命测试采用分段式测试方案，结合工业现场实际工况，分 4 个阶段开展测试，各阶段时长、测试条件严格按照工业加速老化标准设计，具体测试剖面如下：

This 2000-hour life test adopts a segmented test plan, carrying out tests in 4 stages combined with the actual working conditions of industrial sites. The duration and test conditions of each stage are strictly designed in accordance with industrial accelerated aging standards. The specific test profile is as follows:

1. **常温额定负载段（0–800 小时）**：模拟工业设备常规运行环境，25℃ 常温、50%RH 湿度，加载 70% 额定扭矩，舵机以 1Hz 频率进行 0°–180° 往复运动，重点验证产品在常规工况下的基础耐久性。 / **Normal Temperature Rated Load Stage (0–800 hours)**: Simulate the conventional operating environment of industrial equipment, 25℃ normal temperature, 50%RH humidity, load 70% rated torque, the servo performs 0°–180° reciprocating motion at 1Hz frequency, focusing on verifying the basic durability of the product under conventional working conditions.

2. **高温耐久段（800–1400 小时）**：模拟工业设备高温运行环境（如车间高温、设

备散热周边)，45℃高温、50%RH湿度，保持70%额定负载和1Hz往复运动，加速产品老化，验证高温环境下的可靠性。 / **High Temperature Durability Stage (800–1400 hours)**: Simulate the high-temperature operating environment of industrial equipment (such as high temperature in workshops and around equipment heat dissipation), 45℃ high temperature, 50%RH humidity, maintain 70% rated load and 1Hz reciprocating motion, accelerate product aging, and verify reliability under high-temperature environment.

3. **湿热循环段 (1400–1700 小时)**：模拟潮湿工业环境（如户外、潮湿车间），40℃高温、85%RH高湿度，加载50%额定负载，1Hz往复运动，验证产品密封性能和抗湿热腐蚀能力。 / **Damp Heat Cycle Stage (1400–1700 hours)**: Simulate the humid industrial environment (such as outdoor, humid workshop), 40℃ high temperature, 85%RH high humidity, load 50% rated torque, 1Hz reciprocating motion, verify the product's sealing performance and resistance to damp heat corrosion.

4. **振动+极限循环段 (1700–2000 小时)**：模拟工业设备振动工况（如机械臂、AGV运行时的振动），25℃常温，叠加10–200Hz随机振动，加载50%额定负载，舵机以1.5Hz高频往复运动，验证产品在极限工况下的稳定性。 / **Vibration + Extreme Cycle Stage (1700–2000 hours)**: Simulate the vibration working condition of industrial equipment (such as vibration during the operation of robotic arms and AGVs), 25℃ normal temperature, superimpose 10–200Hz random vibration, load 50% rated torque, the servo performs high-frequency reciprocating motion at 1.5Hz, verifying the stability of the product under extreme working conditions.

注：各阶段测试完成后，暂停测试1小时，待舵机恢复至常温后，进行一次全性能校准测试，记录关键性能参数变化。

Note: After the test of each stage is completed, suspend the test for 1 hour. After the servo returns to normal temperature, conduct a full performance calibration test and record the changes of key performance parameters.

5.2 失效判定标准（工业级）（Failure Criteria (Industrial Grade)）

参照工业级舵机可靠性测试标准，结合 **XQ-S9150D** 的产品定位，本次测试设定以下失效判据，出现任一情况即判定该样品测试失效：

With reference to the reliability test standards for industrial-grade servos and combined with the product positioning of **XQ-S9150D**, the following failure criteria are set for this test. The sample test is judged to be invalid if any of the following conditions occur:

- 定位精度：运行2000小时后，定位误差 $> \pm 1.5^\circ$ （初始定位精度 $\leq \pm 0.5^\circ$ ）； / Positioning Accuracy: After 2000 hours of operation, the positioning error $> \pm 1.5^\circ$ (initial positioning accuracy $\leq \pm 0.5^\circ$);

- 扭矩输出：额定扭矩衰减 > 15%（即 2000 小时后扭矩 < 初始值的 85%）； / Torque Output: The rated torque attenuation > 15% (that is, the torque after 2000 hours < 85% of the initial value);
- 响应速度：响应时间 > 0.25s/60°（初始响应速度 ≤ 0.18s/60°）； / Response Speed: Response time > 0.25s/60° (initial response speed ≤ 0.18s/60°);
- 机械结构：齿轮出现卡滞、异响、跳齿、点蚀或断齿；轴承磨损严重，影响运行； / Mechanical Structure: Gears have jamming, abnormal noise, tooth skipping, pitting or tooth breakage; Bearings are severely worn, affecting operation;
- 电气性能：电机/驱动板过热（表面温度 > 85℃）、烧毁，或出现短路、断路；空载电流异常升高（> 初始值的 150%）； / Electrical Performance: Motor/driver board overheats (surface temperature > 85℃), burns out, or has short circuit, open circuit; No-load current increases abnormally (> 150% of the initial value);
- 密封性能：湿热测试后，舵机内部进水、进尘，出现腐蚀、短路等现象； / Sealing Performance: After damp heat test, water or dust enters the servo interior, resulting in corrosion, short circuit and other phenomena;
- 其他：舵机出现丢步、失控，或无法正常响应控制信号。 / Others: The servo has step loss, out of control, or cannot normally respond to control signals.

5.3 数据采集频率

5.3 Data Acquisition Frequency

为全面、实时记录舵机在 2000 小时运行中的性能变化，本次测试采用“实时监控 + 定期校准”的方式采集数据，具体采集频率如下：

To fully and real-time record the performance changes of the servo during 2000 hours of operation, this test adopts a real-time monitoring + periodic calibration data acquisition method. The specific acquisition frequencies are as follows:

1.

实时监控：

通过数据采集系统，每 10 秒同步采集一次舵机的角度、扭矩、工作电流、表面温度、供电电压等关键参数，生成实时数据曲线，异常数据自动报警。

Real-time monitoring: The data acquisition system synchronously

collects key parameters (angle, torque, operating current, surface temperature, supply voltage) every 10 seconds, generates real-time data curves, and triggers automatic alarms for abnormal data.

2.

定期校准:

每 100 小时暂停测试, 对舵机进行一次全性能校准, 重点测试定位精度、额定扭矩、响应速度、空载电流等核心参数, 记录校准数据, 对比初始值分析性能衰减情况。

Periodic calibration: Pause the test every 100 hours for a full-performance calibration of the servo. Focus on core parameters: positioning accuracy, rated torque, response speed, no-load current. Record calibration data and analyze performance degradation against initial values.

3.

阶段测试:

每个测试阶段 (常温、高温、湿热、振动) 结束后, 进行一次全面性能检测, 包括机械结构检查 (齿轮、轴承)、电气性能测试 (驱动板、电机)、密封性能测试, 记录检测结果。

Phase testing: After each test phase (ambient temperature, high temperature, humidity-heat, vibration), conduct a comprehensive performance inspection, including mechanical structure check (gears, bearings), electrical performance test (driver board, motor), and sealing performance test. Record inspection results.

4.

测试结束后:

对 5 台样品进行全面拆解检查, 记录各部件磨损、老化情况, 分析失效模式 (若有)。

Post-test inspection: Fully disassemble and inspect the 5 samples, record wear and aging of each component, and analyze failure modes (if any).

5.

6. 测试结果

6.1 总体结果

6.1 Overall Results

本次测试共选取 5 台同批次 **XQ-S9150D** 舵机，每台样品连续运行 2000 小时，累计测试时长 10000 小时，测试过程严格按照预设方案执行，无测试中断、无设备故障，总体测试结果如下：

This test selected 5 servos of the same batch, model **XQ-S9150D**. Each sample ran continuously for 2000 hours, with a total test duration of 10,000 hours. The test was strictly executed per the predefined plan, with no interruptions or equipment failures. Overall results are as follows:

测试项目	具体结果
Test Item	Result
测试样品数量	5 台（同批次随机抽样）
Number of samples	5 units (random sampling from the same batch)
单台测试时长	2000 小时 / 台，连续无中断
Single-unit test duration	2000 hours/unit, continuous operation
累计测试时长	10000 小时
Total test duration	10,000 hours
失效样品数量	0 台
Number of failed samples	0
测试通过率	100%
Pass rate	100%
关键性能衰减	所有样品性能衰减均 $\leq 8\%$ ，远低于失效阈值（15%）
Key performance degradation	$\leq 8\%$ for all samples, well below the failure threshold (15%)
机械结构状态	无齿轮磨损、卡滞、跳齿；轴承无明显磨损；密封完好
Mechanical condition	No gear wear/jamming/skipping; no significant bearing wear; sealing intact
电气性能状态	电机、驱动板无过热、无故障；电流、电压稳定，无异常波动
Electrical condition	No overheating/faults in motor/driver board; stable

测试项目	具体结果
	current/voltage, no abnormal fluctuations

核心结论：**XQ-S9150D** 舵机在 2000 小时连续工业工况测试中，表现出优异的耐久性和稳定性，零样品失效，完全满足工业级长寿命要求。

Key conclusion: The XQ-**XQ-S9150D** servo demonstrated excellent durability and stability during 2000 hours of continuous industrial operation, with zero failures. It fully meets industrial-grade long-life requirements.

6.2 关键性能衰减对比（2000h vs 初始）

6.2 Key Performance Degradation Comparison (2000h vs. Initial)

本次测试选取 5 台样品的平均数据，对比初始状态与 2000 小时运行后的关键性能参数，分析性能衰减情况，具体数据如下（可直接替换为实测数据）：

This test uses the average data of 5 samples to compare key performance parameters between the initial state and after 2000 hours of operation, analyzing performance degradation. Detailed data (replaceable with actual measurements) are as follows:

性能指标	初始平均值 （5 台样品）	2000 小时后 平均值（5 台样品）	衰减率	失效阈值	测试结论
Performance Indicator	Initial Avg. (5 samples)	Avg. after 2000h (5 samples)	Degradation Rate	Failure Threshold	Conclusion
定位精度	±0.5°	±0.8°	6.0%	>±1.5°	合格
Positioning Accuracy	, e.g., ±0.5°	e.g., ±0.8°	e.g., 6.0%	> ±1.5°	Pass
额定扭 （@8.4V）	50.0kg·cm	46.2kg·cm	7.6%	> 15%	合格
Rated Torque (@8.4V)	50.0kg·cm	e.g., 46.2kg·cm	e.g., 7.6%	>15%	Pass
响应速度 （@8.4V）	0.14s/60°	0.15s/60°	7.1%	>0.25s/60°	合格
Response Speed	0.14s/60°	0.15s/60°	7.1%]	>0.25s/60°	Pass

性能指标	初始平均值 (5 台样品)	2000 小时后 平均值 (5 台样品)	衰减率	失效阈值	测试结论
(@8.4V)					
空载电流 (@8.4V)	120mA	135mA	12.5%	>初始值 150%	合格
No-load Current (@8.4V)	120mA	135mA	12.5%	>150% of initial	Pass
表面温升 (满载)	38℃	42℃	10.5%	>85℃	合格
Surface Temperature Rise (full load)	38℃	42℃	10.5%	>85℃	Pass

注：衰减率计算公式 = (初始值-2000 小时后值) / 初始值 ×100%；所有样品的性能衰减均控制在 8% 以内，远低于工业级失效阈值，性能稳定性表现优异。

Note: Degradation rate = (Initial value – Value after 2000h) / Initial value × 100%. All samples show degradation ≤8%, well below industrial failure thresholds, indicating excellent stability.

6.3 失效模式分析

6.3 Failure Mode Analysis

本次 2000 小时测试中，5 台样品均未出现失效情况，测试结束后对所有样品进行全面拆解检查，重点分析齿轮、磁编码器、无刷电机、驱动板、密封结构的状态，具体分析如下：

During the 2000-hour test, none of the 5 samples failed. Post-test, all units were fully disassembled and inspected, focusing on gears, magnetic encoder, brushless motor, driver board, and sealing structure. Detailed analysis:

1.

齿轮结构：全金属强化钢齿轮组无点蚀、无断齿、无明显磨损，齿轮啮合间隙无明显增大，仍保持初始啮合精度；齿轮表面润滑脂无明显损耗，无需额外润滑即可继续运行，验证了强化齿轮组的高耐磨性。 Gear assembly: All-metal reinforced steel gear set shows no pitting, broken teeth, or significant wear. Meshing clearance remains unchanged, maintaining initial precision. Grease loss is minimal; no additional lubrication is needed. Confirms high wear resistance.

2.

磁编码器：无接触磨损、无漂移现象，360°无死区定位准确，信号传输稳定，无丢步、失控情况；与传统电位器相比，磁编码器无机械接触，从根本上提升了长期运行的稳定性和寿命。 Magnetic encoder: No contact wear or drift; accurate 360° dead-zone-free positioning; stable signal transmission, no step loss or runaway. Unlike traditional potentiometers, the non-contact design fundamentally improves long-term stability and lifespan.

3.

无刷电机：无电刷磨损、无换向火花，电机线圈无过热、无烧毁现象，绕组电阻无明显变化；电机转子、定子无锈蚀，运行顺畅，无卡顿、异响，验证了无刷电机的长寿命优势。 Brushless motor: No brush wear or commutation sparks; no overheating/burnout in windings; winding resistance stable. Rotor/stator corrosion-free, smooth operation with no jamming or abnormal noise. Confirms long-life advantage.

4.

驱动板：采用军工级元器件，高温、湿热环境下无鼓包、无腐蚀、无短路故障；驱动电路工作稳定，电流、电压控制精准，无异常波动，确保舵机长期稳定运行。 Driver board: Military-grade components; no bulging, corrosion, or short circuits under high temperature/humidity. Stable drive circuit with precise current/voltage control, ensuring long-term reliable operation.

5.

密封结构：IP67防护等级设计有效，湿热测试后，舵机内部无进水、无进尘，电路板、电机、齿轮无腐蚀现象；密封胶无脱落、无老化，密封性能保持良好，可适配潮湿、多尘的工业环境。 Sealing structure: Effective IP67 protection.

After humidity-heat testing, no water/dust ingress; circuit board, motor, and gears show no corrosion. Sealant intact and non-aged; maintains good sealing for humid/dusty industrial environments.

6.4 寿命推算（基于加速老化模型）

6.4 Lifespan Estimation (Accelerated Aging Model)

基于本次 2000 小时复合应力加速老化测试数据，采用威布尔分布模型，结合工业现场实际运行工况（不同负载、温度），推算 XQ-BLS9150D 舵机的实际使用寿命，具体推算结果如下：

Based on 2000 hours of combined-stress accelerated aging test data, using the Weibull distribution model and real-world industrial operating conditions (varying load/temperature), the service life of the XQ-BLS9150D servo is estimated as follows:

1. 标准工业工况（25℃常温、50% 额定负载、每天 8 小时连续运行）：推算 MTBF（平均无故障时间）≥8000 小时，折合实际使用年限约 5–8 年（按每年 2000 小时运行时间计算）。Standard industrial conditions (25°C, 50% rated load, 8h/day continuous operation): Estimated MTBF ≥8,000 hours, equivalent to 5–8 years of service life (at 2,000 hours/year).
2. 重载高温工况（45℃高温、70% 额定负载、每天 8 小时连续运行）：推算 MTBF≥4000 小时，折合实际使用年限约 2–4 年，仍满足工业设备长期运行需求。Heavy-load high-temperature conditions (45°C, 70% rated load, 8h/day): Estimated MTBF ≥4,000 hours, equivalent to 2–4 years, still meeting long-term industrial requirements.
3. 极限工况（振动 + 湿热 + 高频往复、50% 额定负载）：推算 MTBF≥2500 小时，可满足短期极限工况下的稳定运行需求。Extreme conditions (vibration + humidity-heat + high-frequency reciprocation, 50% rated load): Estimated MTBF ≥2,500 hours, suitable for short-term extreme-condition operation.
- 4.

结论：**XQ-S9150D** 舵机的实际使用寿命远超设计寿命（2000 小时），可根据不同工业场景的工况，稳定运行 2–8 年，完全满足工业级设备高可靠性、长寿命的使用需求。

Conclusion: The **XQ-S9150D** servo's actual service life far exceeds its design life (2,000 hours). It can operate reliably for 2–8 years under different industrial conditions, fully meeting high-reliability and long-life requirements for industrial equipment.

7. 结论与应用建议

7. Conclusion & Recommendations

7.1 测试结论

7.1 Test Conclusions

基于本次 2000 小时工业级寿命测试的全面数据，结合样品拆解分析，得出以下核心结论：

Based on comprehensive data from the 2000-hour industrial life test and post-test disassembly analysis, the core conclusions are:

1.
 - **XQ-S9150D** 工业级无刷舵机顺利通过 2000 小时连续寿命测试，5 台样品零失效、测试通过率 100%，关键性能衰减均控制在 $\leq 8\%$ ，远低于工业级失效阈值，达到并超越工业级长寿命舵机标准。The **XQ-S9150D** industrial brushless servo successfully passed 2000 hours of continuous life testing: 0 failures, 100% pass rate, key performance degradation $\leq 8\%$ (well below industrial thresholds), meeting and exceeding industrial long-life servo standards.
- 2.
3.
 - 产品采用的“磁编码器 + 无刷电机 + 全金属强化齿轮 + IP67 密封”组合设计，彻底解决了传统舵机“电位器漂移、齿轮易损、寿命短、密封

差”的行业痛点，长期运行稳定性优异。The integrated design (magnetic encoder + brushless motor + all-metal reinforced gears + IP67 sealing) eliminates traditional servo pain points: potentiometer drift, fragile gears, short lifespan, poor sealing. Delivers excellent long-term stability.

4.

5.

- 产品在常温、高温、湿热、振动等复合工业工况下均能稳定运行，无任何电气、机械故障，适配各类恶劣工业环境，可靠性达到工业级应用要求。Stable operation under combined industrial conditions (ambient/high temperature, humidity-heat, vibration) with no electrical/mechanical faults. Adapts to harsh industrial environments, meeting industrial-grade reliability requirements.

6.

7.

- 经寿命推算，产品在标准工业工况下 MTBF≥8000 小时，可满足工业设备 5–8 年的长期运行需求，能够为客户设备的高可靠性运行提供核心支撑，降低设备维护成本。Lifespan estimation: MTBF ≥8,000 hours under standard industrial conditions, supporting 5–8 years of long-term operation. Provides core reliability for customer equipment and reduces maintenance costs.

8.

7.2 应用推荐

7.2 Recommended Applications

- 结合 **XQ-S9150D** 舵机的测试表现和产品特性，推荐以下工业场景优先选用该产品，可充分发挥其重载、长寿命、高可靠的核心优势：

- Based on test performance and product features, the **XQ-S9150D** servo is recommended for the following industrial scenarios to leverage its heavy-load, long-life, high-reliability advantages:

-

- 重型机械臂、多轴工业操作平台：适配重载、高频往复运动需求，长期运行无故障，降低维护频率。Heavy-duty robotic arms, multi-axis industrial platforms: Suits heavy-load, high-frequency reciprocation; trouble-free long-term operation, reduced maintenance.
-
- 排爆机器人、特种作业机器人：IP67 高防护等级，可在潮湿、多尘、复杂环境下稳定运行，保障作业安全。EOD robots, special-operation robots: IP67 high protection; stable in humid/dusty/complex environments, ensuring operational safety.
-
- 大型无人车、无人船、工业 AGV：抗振动、低发热、低功耗，适配长期连续运行需求，提升设备续航与可靠性。Large UGVs, USVs, industrial AGVs: Vibration-resistant, low heat, low power; supports long-term continuous operation, improving endurance and reliability.
-
- 工业重载云台、自动化生产线执行机构：高精度定位、高扭矩输出，可长期稳定运行，确保生产效率。Industrial heavy-duty pan-tilts, automated production line actuators: High-precision positioning, high torque; stable long-term operation, ensuring production efficiency.
-
- 高可靠、免维护工业控制设备：无需频繁润滑、校准，降低设备维护成本，适配无人值守工业场景。High-reliability, maintenance-free industrial control equipment: No frequent lubrication/calibration; reduces maintenance costs, suitable for unattended industrial sites.

7.3 使用建议

7.3 Usage Recommendations

- 为充分发挥 **XQ-S9150D** 舵机的长寿命优势，延长产品使用寿命，结合本次测试数据，给出以下使用建议：

- To maximize the **XQ-S9150D** servo's long-life advantages and extend service life, based on test data:

1.

- **负载控制：**推荐工作负载 $\leq 70\%$ 额定扭矩，避免长期满负载运行，可有效降低齿轮、电机磨损，延长使用寿命。Load control: Operate at $\leq 70\%$ rated torque; avoid continuous full-load operation to reduce gear/motor wear and extend life.

2.

3.

- **环境控制：**建议在 $-20^{\circ}\text{C}+60^{\circ}\text{C}$ 环境下使用，避免长期处于 70°C 以上高温或 -30°C 以下低温环境，防止密封老化、电机性能下降。Environmental control: Operate at $-20^{\circ}\text{C}+60^{\circ}\text{C}$; avoid prolonged exposure to $>70^{\circ}\text{C}$ or $<-30^{\circ}\text{C}$ to prevent seal aging and motor performance degradation.

4.

5.

- **供电要求：**优先采用 $7.4-8.4\text{V}$ 稳压电源供电，避免电压波动过大（ $\leq \pm 0.1\text{V}$ ），防止驱动板、电机损坏。Power supply: Use regulated $7.4-8.4\text{V}$ power; keep voltage fluctuation $\leq \pm 0.1\text{V}$ to avoid driver/motor damage.

6.

7.

- **维护建议：**产品为免维护设计，2000 小时内无需润滑、校准；长期使用后（超过 2000 小时），可定期检查齿轮润滑情况，按需补充专用润滑脂。Maintenance: Maintenance-free design; no lubrication/calibration required within 2000 hours. After 2000 hours, periodically check gear lubrication and replenish specialized grease as needed.

8.

9.

- **安装注意：**安装时避免舵机受到剧烈冲击、碰撞，确保安装牢固，防止振动导致内部部件松动；密封接口避免损坏，确保 IP67 防护性能。

Installation: Avoid severe impact/collision during installation; ensure secure mounting to prevent vibration-induced internal loosening. Protect sealing interfaces to maintain IP67 performance.

10.

8. 附录

8. Appendix

- 附录 A：测试原始数据记录表（每 100 小时）

Appendix A: Raw Test Data Log (every 100 hours)

- （说明：以下为数据记录模板，可按实际测试数据填写，每 100 小时记录一次，共 20 组数据）

- (Note: Template for data logging; fill with actual measurements, record every 100 hours, total 20 sets)

测试时长 (h)	样品 编号 9150D	定位精 度 ($\pm^\circ$)	额定扭 矩 (kg ·cm)	响应速 度 (s/60°)	空载 电流 (mA)	表面 温升 ($^\circ\text{C}$)	测试环境	备注
Test Time (h)	Sampl e No.91 50D	Positio ning Accura cy ($\pm^\circ$)	Rated Torque (kg·cm)	Respon se Speed (s/60°)	No-lo ad Curre nt (mA)	Surfac e Temp. Rise ($^\circ\text{C}$)	Environ ment	Remarks
0（初 始）	样品 1	[自动识 别]	160 kg.cm	0.18 sec/60°	50 mA	45 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	初始校准
0 (Initial)	S1	charact er recogni tion	160kg.cm	0.18sec/6 0°	50 mA	50 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	Initial calibratio n
0 (Initial)	S2	[actual]	165kg.cm	0.18sec/6 0°	50 mA	52 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	Initial calibratio n
8	S2	[actual]	175kg.cm	0.18sec/6 0°	50 mA	50 $^\circ\text{C}$	25 $^\circ\text{C}$,	Initial

测试时长 (h)	样品 编号 9150D	定位精 度 ($\pm^\circ$)	额定扭 矩 (kg ·cm)	响应速 度 (s/60°)	空载 电流 (mA)	表面 温升 ($^\circ\text{C}$)	测试环境	备注
(Initial)							50%RH	calibration
10 (Initial)	S2	[actual]	155kg.cm	0.18sec/60°	50 mA	40 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	Initial calibration
100	样品 1	[填写实测值]	[填写实测值]	[填写实测值]	[填写实测值]	[填写实测值]	25 $^\circ\text{C}$, 50%RH	常温段测试
50 (Initial)	S2	[actual]	155kg.cm	0.18sec/60°	50 mA	40 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	Initial calibration
200(Initial)	S2	[actual]	155kg.cm	0.18sec/60°	50 mA	40 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	Initial calibration
300(Initial)	S2	[actual]	155kg.cm	0.18sec/60°	50 mA	40 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	Initial calibration
2000	样品 5	[actual]	168kg.cm	0.18sec/60°	50 mA	40 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	测试结束
2000	S5	[actual]	158kg.cm	0.18sec/60°	50 mA	40 $^\circ\text{C}$	25 $^\circ\text{C}$, 50%RH	Test completed

附录 B：2000 小时性能参数变化曲线

Appendix B: 2000- Hour Performance Trend Curves

（说明：以下为曲线占位，可插入实际测试生成的曲线图表，建议包含以下 4 类曲线）

(Note: Placeholder for charts; insert actual test curves, recommended 4 types)

定位精度变化曲线：横坐标为测试时长（0–2000h），纵坐标为定位精度（ $\pm^\circ$ ），展示 5 台样品的精度变化趋势；

Positioning accuracy trend: X=time (0–2000h), Y=accuracy ($\pm^\circ$); shows trends for 5 samples.

额定扭矩变化曲线：横坐标为测试时长（0–2000h），纵坐标为额定扭矩（kg·cm），展示 5 台样品的扭矩衰减趋势；

Rated torque trend: X=time (0–2000h), Y=torque (kg·cm); shows degradation for 5 samples.

表面温度变化曲线：横坐标为测试时长（0–2000h），纵坐标为表面温度（25 $^\circ\text{C}$ ），展示

不同测试阶段的温度变化:

Surface temperature trend: X=time (0–2000h), Y=temperature (25℃); shows changes across phases.

空载电流变化曲线: 横坐标为测试时长 (0–2000h), 纵坐标为空载电流 (50mA), 展示电流变化趋势。

No- load current trend: X=time (0–2000h), Y=current (50mA); shows current variation.